MimioView

High-resolution pictures and live video can really engage students and drive home a lesson. And your teachers can do it with plug-and-play simplicity. They take it out of the box, attach a single cord, and it's ready to go. Teachers don't have to learn additional programs because it automatically integrates with MimioStudio™ classroom software, and that means students can begin their learning immediately.

"I love that the teacher or students can mark up a LIVE picture at the whiteboard…"

Cameron Nichols
Elementary School Teacher
Wilmington, NC

Take all the wonder of interactive lessons and activities, and launch them even farther by adding pictures or live video. This is the most user-friendly document camera available. No tangle of wires or endless cords to plug in. One USB plug does it all. The MimioView™ document camera also automatically integrates with MimioStudio software, and instantly captures high-resolution pictures and live video. Teachers can display, freeze, annotate, and save.

- Plug into a single USB computer port for both power and data.
- No external power sources or wall cords.
- Autofocus by pushing a single button.
- Capture both dimensional objects and flat documents.
- Two adjustable light sources.
- Save work by easily annotating images and creating files to use over and over.
- Enjoy exceptional detail with high-resolution 1600 x 1200 imaging.

Zoom or show an angle view, with the convenient gooseneck arm.

To learn more, visit mimio.com/mimioview or call 877.MY.MIMIO.

mimio®
a better way to learn

Specifications

Package Contents

2M Micron camera, microscope adapter, 2 adjustable LED light sources, flexible gooseneck, “micro-B” USB connector (3 m/10 ft), 1 DVD containing MimioStudio classroom software.

Specifications

Minimum Software Requirements
MimioStudio 7 and higher on a Windows, Mac, or Linux OS.

For specific system requirements, please visit us at: mimio.com/support/downloads

Output Resolution
UXGA (1600 x 1200)

Sensor Pixel
2M Micron

Input/Output
USB 2.0 High Speed only

Operation
Single USB cable

Zoom
5.5x mechanical zoom, 16x digital zoom

Lighting
Adjustable LED lighting (x2)

Shooting Area
420 mm x 315 mm when height is 360 mm (16.5 in. x 12.4 in.)

Driver Interface
UVC

User Input
4 Buttons: View, Auto Tune, Rotate, and Freeze

Image Rotation
90-degree increments (CW/CCW)

Macro
Microscope adapter

Overall Weight
1.25 kg (2.8 lb)

Footprint Dimensions
12.7 cm x 14 cm (5 in. x 5.5 in.)

Operating Temperature
5°C to 35°C (41°F to 95°F)

Storage Temperature
-20°C to 55°C (-4°F to 131°F)

Focus
Automatic

Color Balance
Automatic

Video and Images
Save to MimioStudio Gallery

Content Alignment
Straightedge incorporated on base

Camera Adjustment
Flexible gooseneck for camera

Certification & Compliance
Safety & EMC: FCC (U.S.), IC (Canada), CE (Europe), GOST-R (Russia), VCCI (Japan), C-tick (Australia/New Zealand), KCC (Korea), CQC (China). Environmental: RoHS, WEEE.

Warranty and Support
Mimio hardware is warranted for 2 years from date of purchase, with an additional 3 years with product registration at mimio.com/warranty, for a total of 5 years. MimioStudio software is supplied with a limited lifetime warranty, expiring 1 year after discontinuation of the product.

To learn more, visit mimio.com/mimioview or call 877.MY.MIMIO.

mimio®
a better way to learn

© 2012 Mimio, a Newell Rubbermaid company